












## 夏普LED专用驱动电源 SHARP LED Driver

SHARP LED Part Number	产品型号 Model	产品图片 Product Picture	工作电压 Voltager range	恒流及精度 Output current	效率 Efficiency	功率因数 Power Factor	输出电压 Output voltage	外型尺寸 Contour Size	可否调光 with the dimmer
BMC	TXM01-0104-XX		AC90-240V	350MA±5%	>70%	>0.50	DC=9-11V	27*17*17mm	
BMC	TXM02-0402-XX		AC90-240V	440MA±5%	>72%	>0.55	DC=9-11V	30*18*17mm	
BMC	TXM03-0500-XX		AC90-240V	300MA±5%	>74%	>0.55	DC=9-11V	28*17*14mm	
BMC	TXM04-0501-XX		AC90-240V	300MA±5%	>70%	>0.51	DC=9-11V	27*16*14mm	
BMC	TXM05-0500-XX		AC90-240V	300MA±5%	>60%	>0.50	DC=9-11V	∅21*14mm	
BMC	TXM36-0500-XX		AC90-240V	300MA±5%	>70%	>0.50	DC=9-11V	40*15*11mm	
BMF	TXM06-0200-XX		AC90-240V	300MA±5%	>70%	>0.50	DC=12-17V	46*17*22mm	
BMF	TXM08-0301-XX		AC90-240V	500MA±5%	>80%	>0.80	DC=16-21V	58.5*23.5*22.6mm	
BMF	TXM10-0205-XX		AC90-240V	450MA±5%	>80%	>0.90	DC=15-17V	55.3*22.4*21.5mm	
BMF	TXM12-0301-XX		AC90-240V	500MA±5%	>80%	>0.80	DC=12-20V	68*21.5*20mm	
BMF	TXM27-0604-XX		AC180-240V	480MA±5%	>78%	>0.70	DC=10-14V	55*22*21mm	yes
BMF	TXM27-0606-XX		AC90-130V	480MA±5%	>78%	>0.65	DC=10-14V	55*22*21mm	yes

BMF	TXM30-0209-XX		AC90-240V	330MA±5%	>77%	>0.50	DC=12-18.5V	43*17*19mm	
BMF	TXM30-0209-XX		AC90-240V	440MA±5%	>77%	>0.50	DC=10-13.5V	43*17*19mm	
BMF	TXM30-0209-XX		AC90-240V	480MA±5%	>77%	>0.50	DC=10-13.5V	43*17*19mm	
BMF	TXM16-0301-XX		AC90-240V	500MA±5%	>80%	>0.80	DC=14-20V	ø57*17mm	
BMJ	TXM12-0302-XX		AC90-240V	450MA±5%	>80%	>0.86	DC=19-24V	68*21.5*20mm	
BMJ	TXM16-0302-XX		AC90-240V	290MA±5%	>80%	>0.85	DC=18-24V	ø57*17mm	
BMJ	TXM27-0605-XX		AC180-240V	300MA±5%	>75%	>0.65	DC=15-23V	55*22*21mm	yes
BMD BMK BMU	TXM06-0203-XX		AC90-240V	115MA±5%	>75%	>0.50	DC=30-42V	46*17*22mm	
BMD BMK BMU	TXM06-0203-XX		AC90-240V	150MA±5%	>80%	>0.52	DC=30-42V	46*17*22mm	
BMD BMK BMU	TXM06-0203-XX		AC90-240V	180MA±5%	>80%	>0.52	DC=30-42V	46*17*22mm	
BMD BMK BMU	TXM10-0207-XX		AC90-240V	200MA±5%	>80%	>0.90	DC=35-45V	55.3*22.4*21.5mm	
BMD BMK BMU	TXM12-0304-XX		AC90-240V	210MA±5%	>80%	>0.85	DC=40-50V	68*21.5*20mm	
BMD BMK BMU	TXM16-0304-XX		AC90-240V	290MA±5%	>80%	>0.85	DC=35-40V	ø57*17mm	

BMU	TXM10-0207-XX		AC90-240V	200MA±5%	>80%	>0.90	DC=35-45V	55.3*22.4*21.5mm	
15W	TXM19-0700-XX		AC90-240V	400MA±5%	>80%	>0.85	DC=40-50V	68*23.5*24mm	
15W	TXM11-0700-XX		AC90-240V	450MA±5%	>90%	>0.90	DC=35-50V	53*51*24mm	
15W	TXM14-0701-XX		AC180-240V	450MA±5%	>80%	>0.85	DC=35-45V	58*51*26mm	yes
15W	TXM28-0705-XX		AC180-240V	300MA±5%	>78%	>0.80	DC=35-45V	68*27*21mm	yes
15W	TXM33-0700-XX		AC90-240V	450MA±5%	>80%	>0.90	DC=35-45V	ø52*20mm	
25W	TXM11-0703-XX		AC90-240V	700MA±5%	>80%	>0.90	DC=30-40V	53*51*24mm	
25W	TXM14-0704-XX		AC180-240V	600MA±5%	>80%	>0.80	DC=35-45V	58*51*26mm	yes
25W	TXM19-0703-XX		AC90-240V	700MA±5%	>80%	>0.90	DC=30-40V	68*23.5*24mm	
25W	TXM28-0705-XX		AC180-240V	300MA±5%	>78%	>0.80	DC=35-45V	68*27*21mm	yes
25W	TXM33-0701-XX		AC90-240V	600MA±5%	>80%	>0.80	DC=35-45V	ø52*20mm	