































CICIZEN LED 电源选型

CITIZEN LED Part Number	产品型号 Model	产品图片 Product Picture	工作电压 Voltage range	恒流及精度 Output current	效率 Efficiency	功率因数 Power Factor	输出电压 Output voltage	外型尺寸 Contour Size	可否调光 with the dimmer
CL-L103	TXM01-0104-XX		AC90-260V	350MA±5%	>73%	>0.50	DC=9-11V	27*17*17mm	
CL-L103	TXM03-0500-XX		AC90-260V	300MA±5%	>74%	>0.55	DC=9-11V	28*17*14mm	
CL-L103	TXM04-0501-XX		AC90-260V	300MA±5%	>75%	>0.51	DC=9-11V	27*16*14mm	
CL-L103	TXM05-0500-XX		AC90-260V	300MA±5%	>60%	>0.50	DC=9-11V	∅21*14mm	
CL-L103	TXM06-0200-XX		AC90-260V	300MA±5%	>77%	>0.50	DC=12-17V	46*17*22mm	
CL-L103	TXM30-0209-XX		AC90-260V	440MA±5%	>77%	>0.50	DC=10-13.5V	43*17*19mm	
CL-L103	TXM30-0209-XX		AC90-260V	480MA±5%	>75%	>0.50	DC=10-13.5V	43*17*19mm	
CL-L251	TXM02-0404-XX		AC90-260V	500MA±5%	>73%	>0.56	DC=9-11V	30*18*17mm	
CL-L251A	TXM06-0203-XX		AC90-260V	115MA±5%	>75%	>0.50	DC=28-42V	46*17*22mm	
CL-L251A	TXM06-0203-XX		AC90-260V	150MA±5%	>80%	>0.52	DC=30-42V	46*17*22mm	
CL-L251A	TXM06-0203-XX		AC90-260V	180MA±5%	>80%	>0.52	DC=30-42V	46*17*22mm	
CL-L251A	TXM10-0207-XX		AC90-260V	200MA±5%	>80%	>0.95	DC=35-45V	55.3*22.4*21.5mm	

CL-L251(6W)	TXM08-0300-XX		AC90-260V	700MA±5%	>80%	>0.80	DC=10-13V	58.5*23.5*22.6mm	
CL-L103(6W)	TXM12-0300-XX		AC90-260V	700MA±5%	>80%	>0.80	DC=10-13V	68*21.5*20mm	
CL-L103(6W)	TXM16-0300-XX		AC90-260V	700MA±5%	>80%	>0.80	DC=10-13V	ø57*17mm	
CL-L103(6W)	TXM18-0300-XX		AC90-260V	700MA±5%	>80%	>0.80	DC=10-13V	48*29*20mm	
CL-L253E	TXM07-0600-XX		AC90-260V	330MA±5%	>85%	>0.85	DC=21-30V	58.5*23.5*22.6mm	
CL-L253E	TXM12-0302-XX		AC90-260V	450MA±5%	>80%	>0.86	DC=19-24V	68*21.5*20mm	
CL-L253E	TXM16-0302-XX		AC90-260V	290MA±5%	>80%	>0.85	DC=18-24V	ø57*17mm	
CL-L253E	TXM18-0302-XX		AC90-260V	450MA±5%	>80%	>0.85	DC=18-24V	48*29*20mm	
CL-L233	TXM11-0703-XX		AC90-260V	700MA±5%	>80%	>0.90	DC=21-30V	53*51*24mm	
CL-L233	TXM19-0703-XX		AC90-260V	700MA±5%	>80%	>0.90	DC=21-30V	68*23.5*24mm	
CL-L233	TXM33-0703-XX		AC90-260V	700MA±5%	>80%	>0.90	DC=21-30V	ø52*20mm	
CL-L234A	TXM11-0702-XX		AC90-260V	670MA±5%	>80%	>0.90	DC=35-45V	53*51*24mm	
CL-L234A	TXM14-0704-XX		AC180-260V	600MA±5%	>80%	>0.80	DC=35-45V	58*51*26mm	yes

CL-L234A	TXM17-0702-XX		AC90-260V	670MA±5%	>80%	>0.90	DC=35-45V	75*39*27mm	
CL-L234A	TXM33-0702-XX		AC90-260V	670MA±5%	>85%	>0.90	DC=35-45V	ø52*20mm	
CL-L234A	TXM19-0702-XX		AC90-260V	600MA±5%	>80%	>0.80	DC=35-45V	68*23.5*24mm	
CL-L330	TXM14-0702-XX		AC180-260V	670MA±5%	>85%	>0.90	DC=35-45V	58*51*26mm	yes
CL-L330	TXM14-0704-XX		AC180-260V	600MA±5%	>85%	>0.80	DC=35-45V	58*51*26mm	yes
CL-L330	TXM17-0702-XX		AC90-260V	670MA±5%	>85%	>0.90	DC=35-45V	75*39*27mm	
CL-L330	TXM33-0702-XX		AC90-260V	600MA±5%	>85%	>0.80	DC=35-45V	ø52*20mm	yes